

DigiDriver IP

IP65 control and power unit for running video pixel products

ORDER CODE: **DIGIDRIVERIP**



DigiDriver IP is a driver which provides power and processing to the **DigiStrip IP**. It has 2 outputs and can control up to 20 **DigiStrip IP100** and 40 **DigiStrip IP50** - each offering the control of up to 3.600 pixels in a one rack unit, offering 20 DMX universes and 546 W of power in and out. **DigiDriver IP** cannot control **DigiStrip**, **DigiTube** and **DigiTile**. **DigiDriver IP** is compatible with Art-Net, Kling-Net and sACN protocols and runs signal and power over a 4 pole XLR cable that allow wiring of units in a chain. The user interface consists of a black OLED display for settings, protocol selection, network address and test patterns. IP 65 rating allows for the usage at outdoor events so humidity and rain are no longer a worry

MAIN FEATURES

- Art-Net, Kling-Net and sACN control protocol supported
- Power and signal output up to 20 DigiStrip IP100 and 40 DigiStrip IP50
- IP65 for outdoor events

TECHNICAL SPECIFICATION

BODY

- Hardware on-board: Included rack-mount hardware
- Body: sturdy die-cast aluminium body conceived for long-time durability
- Body colour: black
- Other: 2U rack

CONTROL

- Control units: 20 x DIGISTRIP100 or 40 x DIGISTRIP50
- Art-Net channels: 20x512ch
- Protocols: Art-Net, Kling-Net, sACN
- Pixel control: pixel2pixel control
- Display: black OLED high resolution display

ELECTRONICS

- Operating temperature: -20° ~ +45°


ELECTRICAL

- Power supply: 100-240 V – 50/60 Hz
- Power consumption (at 230 V): 546W
- Power consumption (at 120 V): 570W
- Output (at 230 V): 5 units on a single power line
- Output (at 120 V): 2 units on a single power line

PHYSICAL

- Cooling: passive cooling and fan-free
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: 2xRJ45 and 4p out
- Power connection: Seetronic powerCON waterproof IN/OUT connectors
- IP rating: 65 for temporary outdoor application, not for fixed installation
- Dimensions (WxHxD): 483x84x250mm
- Weight: 4.5kg

TECHICAL DRAWINGS



For more product
info and downloads
visit our website



PROLIGHTS is a trademark of
MUSIC & LIGHTS S.r.l.
musiclights.it

Via A. Olivetti snc
04026 - Minturno (LT) ITALY
Tel: +39 0771 72190

prolights.it
info@prolights.it