

BASSO118 18" ultra-high power infra-subwoofer

Highlights:

- · 3000 Watt program power
- · Low frequency extension down to 23Hz without processing
- 128 dB of Max SPL (continuous)
- Indoor model with Polyurea coated 18/36mm multiply plywood
- Weather resistant with marine grade plywood and Dura-Polyurea coating
- · Extremely ridged chassis and inner framing

Product information:

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion.

Applications:

- · Bars & Restaurants
- Hotels
- Clubs
- · Sporting facilities
- · Events
- · Concert venues
- · Museums & Themeparks









Properties:

ॐ- Weatherproof

Impedance:

 Ω 80hm

Usage:



Indoor & Outdoor

System specifications:

Speaker type		18" Infra-Sub		
Configuration		AeroVent		
Peak power handling		6000 W		
Program power handling		3000 W		
Continuous power (AES)		1500 W		
Impedance		8 Ω		
Max SPL (Continuous)		131 dB		
Sensitivity (1W/1m)		99 dB		
Frequency	Response (- 3 dB)	30 Hz - 120 Hz		
	Range (-10 dB)	23 Hz - 200 Hz		
Bass port tuning frequency		33 Hz		
Connectors		Terminal block with linkthrough		
Drivers		18" carbon cone with dual suspension (low-loss) and 4" high excursion voice coil		
Ingress Protection rating		IP55 (BASSO118/OB)		

Product Features:

Dimensions		$758 \times 550 \times 798 \text{ mm (W} \times H \times D)$ (excluding feet)	
		758 x 555 x 798 mm (W x H x D) (including feet)	
Weight		45 kg	
Operating temperature		-20 °C ~ 70 °C	
Construction		18 mm Multiply Plywood with multi-layer Polyurea coating	
Front finish		2.5 mm Steel grill with hexagon perforations and acoustic foam backing	
Mounting & handling	Rigging points	12 x M10 mounting bracket installation holes on both sides	
	Stand fitting	1 x M20 internal thread stand adapter	
Colours		Black	

Variants:

- BASSO118/B Black version
- BASSO118/OB Outdoor black version

Shi	nn	ing	X, (`)rc	ÞΓ	ino:
2111	P٢	1116		71 0		'' 'B.

Packaging	Cardboard box
Shipping weight & volume	50 kg - 0.46 Cbm