

Connection module - Charger module with USB type A and type C

The CP45PUSB is a 45 x 45 mm charger module with one USB type A and type C output socket available in black color & 2 versions. This module is compatible with CAYMON CASY303 and standard 45 x 45 mm mounting frames and cover plates.



	CP45PUSB/B	CP45PUSB65/B
Input voltage	100-240V AC / 50-60 Hz	
Total output power	Max. 20 W	Max. 65 W
Output voltage (Type-A)	5V / 2.1A	5V / 3A / 5V / 2A / 5V / 1.5A
Output voltage (Type-C)	5V / 3A	5V / 3A / 5V / 2A / 5V / 1.5A
Dimensions (mm)	45 x 45 x 38 mm	45 x 45 x 47 mm

Product Features:

Dimensions

45 x 45 x 38 mm (W x H x D) (CP45PUSB/B)

45 x 45 x 47 mm (W x H x D) (CP45PUSB65/B)

Electrical Characteristics:

Input voltage		100 ~ 240 V AC / 50 ~ 60 Hz
Total output power		Max. 20 W (CP45PUSB/B)
		Max. 65 W (CP45PUSB65/B)
Output voltage	Type-A	5V / 2.1A (CP45PUSB/B)
	Type-C	5V / 3A (CP45PUSB/B)
	Type-A	5V / 3A (CP45PUSB65/B)
		9V / 2A (CP45PUSB65/B)
		12V / 1.5A (CP45PUSB65/B)
	Type-C	5V / 3A (CP45PUSB65/B)
		9V / 3A (CP45PUSB65/B)
		12V / 3A (CP45PUSB65/B)
		15V / 3A (CP45PUSB65/B)
		20V / 3.25A (CP45PUSB65/B)
Supported standards		Type-A - USB QC3.0 (CP45PUSB65/B)
		Type-C - USB PD (CP45PUSB65/B)

Variants:

- CP45PUSB/B - Black version - 5V/4200 mA
- CP45PUSB65/B - Black version - 65W 20V/3.25A