



WP210

Universal wall panel - Microphone & line input - 80 x 80 mm

Highlights:

- Elegant design to blend in with any environment
- Compatible with EU (80x80 mm) installation materials
- Signal transmission over twisted pair (CAT5E) or better cabling
- Signal transmission insensitive for interference and noise

The WP210 is a remote wall mixer that can be used in combination with various AUDAC hardware (ARES5A, MTX series, AMP523 and more). It converts the signal coming from a stereo line-level audio source (such as a tuner, mobile devices, ...) or balanced microphone to the level corresponding to the differential signal input making it possible to transfer high-quality audio over long distances between the wall panel and the loudspeaker, by just using inexpensive twisted-pair CAT5e or better cabling. On the front side of the wall panel, there is a 3.5 mm jack stereo line input connection available together with a balanced XLR microphone input, both provided with their own knob which allows the signals to be mixed together.

The WP210 is available in 2 colours (White - RAL9003 & Black - RAL9005) and is compatible with most standard EU (80x80 mm) style in-wall boxes for solid and hollow walls. With the Elegant ABS front panel with glass, it will blend into any environment



System specifications:


Outputs	Level	+12 dB
		0 dB
Inputs	Wall Panel	Type
		3.5 mm jack stereo line input connection
		XLR microphone input connection
		Mic & Line inputs on rear for permanent connections
Connection		3.5 mm jack input (Stereo line input)
		Female XLR input connector (Microphone input)
		6-pin terminal block (3.81 mm pitch) input connection on rear (duplicated line & mic inputs)
		8-pin terminal block (3.81 mm pitch) output connection
Control		Individual input level control for Mic & Line
		Phantom power (DIP switch on rear)
		Low-cut (Mic) enable / disable (DIP switch on rear)
		Mono / Stereo (DIP switch on rear)

Product Features:

Dimensions		80 x 80 mm (W x H) (Remote wall panel)
Colours		Black (RAL9005) (WP210/B)
		White (RAL9003) (WP210/W)
Front finish		Elegant ABS front panel with glass
Accessories	Optional	Flush mount Installation boxes
		Flush mount box for 45 x 45 mm wall panel - Solid wall - WB45S/FS
		Flush mount box for 45 x 45 mm wall panel - Hollow wall - WB45S/FG

Standards & regulations:

CE	LVD	Compliant to EN 62368
	EMC	Compliant to EN 55032, EN55024, EN 61000-3-2/3
CB		Compliant to IEC 62368
FCC		Part 15C
cTUVus		Compliant to IEC 62368+UL62368
RoHS		Compliant
Reach compliant		Compliant



WP210		Product description
MM [INCH]	Weight	REMOTE WALL PANEL INPUT – MIC + LINE – 80x80 MM
80 x 80 x 57,1 mm 3,15 x 3,15 x 2,248 "	TBA TBA	Outer dimensions (w x h x d) Unit height N/A