

# Jet Spot2

150 W moving spot with white LED source

ORDER CODE: JETSPOT2



**Jet Spot2** is a LED spot luminaire designed to deliver a stunning light level for its size and price. Ideal both for installation and for rental, the **Jet Spot2** focuses on maximising the light output from its LED source to deliver a crisp, even beam from a compact size.

## MAIN FEATURES

- Ultra-efficient 150 W 8.000 K white LED source
- Fixed 20° beam angle
- Extensive effects including one colour wheel, rotating gobo wheel, static gobo wheel, prism and focus

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 150 W high-power white LED
- CCT: 8.000 K
- CRI: 78
- Luminous flux: 7'400 lm
- Lux: 8'900 lx @3 m
- Lux: 810 lx @10 m
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 20°
- Focus: motorised

### COLOUR SYSTEM

- Colour wheel: 8 dichroic filters + open

### DYNAMIC EFFECTS

- Rotating gobos: 7 rotating gobos + open, interchangeable, indexing
- Gobo size: outer: 24,2 mm - image: 20 mm - thickness: 0,3 mm
- Fixed gobos: 8 fixed gobos + open
- Circular prism: 3f with bi-directional rotation, indexing
- Auto mode: built-in programs with execution speed adjustment

### BODY

- Pan angle: 540°
- Tilt angle: 270°
- Pan/Tilt resolution: 8 / 16 bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with hi-resistance polycarbonate cover
- Body colour: black, white finishing available

### CONTROL

- Protocols: DMX512, RDM
- DMX channels: 12 / 15 channel
- RDM: RDM ready for fixture remote monitor and settings
- Display: black OLED high resolution display
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronized operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: -10° ~ +45°

### ELECTRICAL

- Power supply: 100-240 V – 50/60 Hz
- Power consumption (at 230 V): 225 W
- Power consumption (at 120 V): 226 W
- Output (at 230 V): 16 units on a single power line
- Output (at 120 V): 8 units on a single power line

### PHYSICAL


- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: XLR 3p + 5p IN/OUT connectors
- Power connection: Seetronic powerCON IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 308x436x230 mm
- Weight: 13,7 kg

## ACCESSORIES & RELATED PRODUCTS


- FCLJET2: Flight case per 4 pcs of JETBEAM2 / JETSPOT2

## COLOUR PRESET FULL ON

Beam angle 20°



## TECHICAL DRAWINGS



PROLIGHTS is a trademark of  
MUSIC & LIGHTS S.r.l.  
[musiclights.it](http://musiclights.it)

Via A. Olivetti snc  
04026 - Minturno (LT) ITALY  
Tel: +39 0771 72190



For more product  
info and downloads  
visit our website



[prolights.it](http://prolights.it)  
[info@prolights.it](mailto:info@prolights.it)