

CS1000S

In-Wall Subwoofer

AUDAC

► Features

- Superb reproduction of low frequencies
- Easy installation
- Slim design speaker
- Paintable into any RAL colour
- Light-weight subwoofer
- High power and sound pressure level
- Moisture proof

► Applications

- Halls
- Pubs
- Restaurants
- Stores
- Warehouses



In addition to the CS series, AUDAC created the CS1000S 10" in-wall/ceiling subwoofer speaker with a super slim design.

With a built-in depth of merely 104 mm, you can fit the CS1000S into almost every wall or ceiling, and as all other CS speakers, the CS1000S can be painted to blend in with the structure the speaker is built-in.

The CS1000S has a superb reproduction of the low frequencies and therefore is ideal to use in combination with your WS series in-wall or CS series ceiling speakers.

The cone of the speaker is treated to be completely moisture proof, so it can also be used in damp rooms or outside applications.

The CS1000S features a 10" low frequency range woofer with an output power of 100W RMS at 8 Ohm and a maximum power of 200W. It can produce a sound pressure level up to 114 dB and has a stunning frequency response of 28 Hz to 300 Hz.

The CS1000S is made of strong ABS and equipped with the necessary installation clamps for easy mounting.

Any colour from the RAL list can be chosen at additional cost.

► Specifications

SYSTEM SPECIFICATIONS	
Max power	200 W
RMS power	100 W
Impedance speaker	8 Ohm
Sound pressure 1W/1m	88 dB
Sound pressure Max W/1m	108 dB
Frequency response -3dB	50 Hz - 250 Hz
Frequency range -10dB	28 Hz - 300 Hz
Cross-over frequency	250 Hz
Crossover network	Passive built-in
Horizontal coverage	180°
Vertical coverage	180°
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	304 x 304 x 104 mm
Cut-out measurements	270 x 270 mm
Built-in depth	70 mm
Weight net	3.6 Kg
Drivers	10" LF
Connectors	Cable clamps
Construction	ABS
Front finish	White aluminium grill
Mounting	Claw clamps
Colour	White (RAL 9010)
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	4.5 Kg - 0.0134 Cbm
Accessory included	Mounting brace
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	