

Mini Ruby

132W discharge moving beam with white HID source

ORDER CODE: **MINIRUBY**

TRIBE



Mini **Ruby** is an ultra-compact beam light that harnesses all the power of its Osram Sirius 132W lamp into a tight, bright and sharp 3,5° beam. Its small form factor is designed to allow the users to apply a discharge beam light in tight locations or low ceilings bringing a big punch to a small space.

MAIN FEATURES

- 9 position colour wheel.
- Compact, lightweight design for use in small spaces.
- Rotating 8 facet prism.

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 132W S Osram Sirius HRI
- CCT: 9.200 K
- Luminous flux: 5'150 lm
- Lux: 98'792 lx @5 m full
- CRI: 60
- Source life expectancy: 6.000 h

OPTICS

- Beam angle: 3,5°
- Field angle: 3,5°
- Lens diameter: 80 mm
- Lens type: high-quality glass lens optics

COLOUR SYSTEM

- Colour wheel: 9 colour filters

DYNAMIC EFFECTS

- Circular prism: 8f with bi-directional rotation

BODY

- Pan angle: 540 / 630°
- Tilt angle: 265°
- Pan/Tilt resolution: 8 / 16bit
- Feedback: automatic repositioning after accidental movement
- Body: aluminium structure with hi-resistance polycarbonate cover
- Body colour: black

CONTROL

- Protocols: DMX512, RDM
- DMX channels: 7 / 9 channel
- Display: LCD display
- Firmware upgrade: yes, via USB - DMX interface (UPBOX2) not included
- Hibernation: power safe mode when lost DMX
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Strobe / shutter: 1 - 28 flash(s), mechanical
- Operating temperature: -10° ~ +45°

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 176W
- Max power consumption (at 120V): 176W
- Output (at 230V): 12 units on a single power line

PHYSICAL

- Cooling: combination of heat pipe cooling system and low noise fan
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: Amphenol XLR 3p + 5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 278x387x200 mm
- Weight: 7,6 kg

ACCESSORIES & RELATED PRODUCTS

- OSHR132W Sirius HRI 132W 1.9A discharge lamp (included)
- FCLMINIRUBY Flight case for 6 pcs of MINIRUBY

- OS24 Quick-lock omega bracket. (included)
- UPBOX2 Firmware uploader kit, USB IN, 3-pin XLR DMX OUT