



## Highlights:

- · IP65 Ingress protection
- 12" high output woofer with a 1.8" voice coil
- Multi-Layer glass composite material with textured EPDM black coating
- · Barrier terminal block in waterproof connection box

The AUDAC HS212MK2 is a full-range loudspeaker system engineered to provide long throw, full range sound projection in a variety of fixed in- and outdoor applications. Its wide, smooth frequency response and high efficiency ensure high-fidelity music reproduction along with superb projection of clear, intelligible speech at very low distortion. The HS212MK2 features a 1,8" HF driver with an 12" LF loudspeaker combination for the best sound reproduction and has a very special coverage pattern of 40° horizontally and vertically. The construction of the HS212MK2 is made of polyester with textured EDPM black coating and a perforated aluminum grill front finish. Behind the aluminum grill, there is an acoustic foam assembled, which prevents rain coming into the speaker. Due to an Ingress Protection rating (IP) of 54, this speaker will be suitable for any environment where humidity or moisture are present. For connecting, two speaker connectors are provided. The second connector can be used for linking through the signal to other speaker cabinets. Mounting brackets: - MBK212Z (Stainless Steel)

#### **Applications:**

- · Sport facilities
- Events
- · Corporate spaces





#### Certification:



### Impedance:



# System specifications:

Speaker type		2-way horn speaker
Max. Power		700 W
RMS Power		350 W
Impedance		8Ω
Sensitivity (1W/1m)		95 dB
Sound Pressure (Max. W/1m)		125 dB
Frequency	Response (± 3 dB)	80 Hz - 18 kHz
	Range (-10 dB)	65 Hz - 20 kHz
Crossover	Frequency	1.5 kHz
	Туре	Passive built-in
Dispersion	Horizontal	40°
	Vertical	40°
Ingress Protection rating		IP54
Connection		2 x heavy-duty SpeakON NLT4MPBAG (linkthrough)
Drivers	HF	1.8" Neodymium compression driver
	MF	12"

## Product Features:

Dimensions	508 x 508 x 732 mm (W x H x D)
Weight	30.800 kg
Construction	Multi-Layer glass composite material with textured EPDM black coating
Front finish	Powdercoated aluminium with lining
Mounting & handling	Mounting bracket fixing holes
Colours	Black (RAL9005)