



	PROLIGHTS Astra Profile400	PROLIGHTS Jet Profile300LT
PRICE	€4,515.00	2.600 Eur
Light Source	400W white LED	300W White LED
Source CCT	7,000K	6,500K
Beam Angle	6,5° (50%) - 50° (10%)	* 3,9° - 44,1°
Peak Lumens (lm)	17,598lm (50°), 9,143lm (6,5°)	* 12'065 lm @44,1° * 8'313 lm @3,9°
Peak Intensity (lx)	* 37,468 lux @5mt (6,5°) * 1,690 lux @ 5mt (50°)	* 88'597 lx @5m @3,9° * 1'282 lx @5m @44,1
Colour system	Linear CMY and colour wheel CRI+CCT correction filter included	Linear CMY and 3 independent colour wheels with 3 dichroic filters each one + open
CCT	2,700K – 7,000K	filters on wheel (3.200 K, 4.500 K and 5.600K)
Gobos	7 rotating gobos	7 rotating interchangeable gobos + open
Shutters	4 blades with 30° angle adjustment and 45° rotation	4 blades with +/-30° angle adjustment and +/-45° rotation
Prism	4f circular with bi-directional rota- tion	4f circular with bi-directional rotation 4f linear with bi-directional rotation
Animation wheel	YES	YES
Frost	YES	Soft-edge filter on-board, interchangeable. Heavy frost filter (optional).
Control Protocols	DMX, RDM, ArtNet, sACN, W- DMX, CRMX	DMX, RDM,
Wireless	W-DMX, CRMX	CRMX
LED Frequency	600Hz-50KHz	600 Hz - 50 KHz
GUI	High-res LCD colour display	
Operating Temperature	-10° / +45°	
Connections	True1 In/out, XLR5p In/out, Ether- net in/out	True1 In/out, XLR5p In/out, USB port
IP rating	IP20	IP20
Max Power consumption	620W	491W
Weight	27.6Kg	21,4 kg